

SAFETY DATA SHEET

Farbatone®

PRODUCT NAME: PEVA-S
PRINT DATE: 20-03-22
VERSION:1.0

SECTION 1: IDENTIFICATION OF PRODUCT AND COMPANY/UNDERTAKING

Product Name	PEVA-S
Use	Screen printing ink
Company Name	Spinks India
Company Address	Plot No. 135,Pace city-1, sec-37 ,Gurgaon-122001, Haryana, India
Department responsible Contact email id/ Telephone	Product safety psm@spinksworld.com +91-124-4770500

SECTION 2: HAZARD IDENTIFICATION

Hazard Warnings for Environment	There is the pollution to the water body, there is danger to the environment.
Physical and Chemical Dangerous	When being living over flashing point either the flashing point temperature, gas of divulgence either liquid easily formation flammability mixture, There is inflammation detonation peril.
Hazard Category	3.3rd type tall flashing point easily ignite liquid
Invasion method	Breathe in Food is entered Suck Up after the hide
Hazard Warnings: for Health	The aperture be able to be created, S k i n , S t i c k the membrane irritate, Skin is arid; Narcosis of nerve Centre, Man's lethargic sleep and dizziness is cause.

SECTION 3: COMPOSITION / INGREDIENT INFORMATION

Mixture

Chemical character- Ink

Components Name	Concentration/Percentage	CAS NO.
Anone	10-15%	108-94-1
Hemellitene	10-15%	108-67-8
Isophorone	3%	78-59-1

SAFETY DATA SHEET



PRODUCT NAME: PEVA-S
PRINT DATE: 20-03-22
VERSION:1.0

SECTION 4: FIRST AID MEASURES

Skin Contact

Remove contaminated clothing and shoes

Immediately wash skin with plenty of water and soap for at least 15 minutes and get medical attention

Eye Contact

Immediately and thoroughly flush the eye with large amounts of water at least 15 minutes and get medical attention.

If not removed promptly, this material may cause serious eye damage.

Part eyelids with fingers to assure complete flushing.

Check for and remove contact lenses if easily possible.

Ingestion

Do not induce vomiting. Get medical attention immediately.

Rinse mouth with water if possible.

Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration.

If breathing is difficult, give oxygen.

Keep the affected person warm and at rest. Get Medical attention immediately.

SECTION 5: FIRE – FIGHTING MEASURES

Extinguishing Media	Water fog, foam, dry chemicals, CO2, dry sand
Extinguishing Media which must not be used	Water Jet
Fire Fighting Instruction	Keep unnecessary and unprotected personnel away Shut off supply if possible. Remove containers to safe place if possible. Keep containers and surroundings cool by spraying with water. Fight fire from an upwind position
General Hazard	Flammable liquid and vapour. Vapours may form and explosive mixture with air. The vapour is heavier than air and can accumulate near the ground

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precaution	Keep unnecessary and unprotected personnel away. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 9. Keep upwind, evacuate people downwind.
Environmental Protections	Do not let this chemical enter the environment
Clean-up Methods	Use non-sparking tools and equipment Absorb or cover with dry earth, sand or other non-combustible material and transfer to sealable containers. Large spills: Dike far ahead of liquid spill for later disposal.

SAFETY DATA SHEET



PRODUCT NAME: PEVA-S
PRINT DATE: 20-03-22
VERSION:1.0

SECTION 7: HANDLING AND STORAGE

Technical Measures	Use only with adequate ventilation. Keep away from heat, spark and flame. Use explosion-proof electrical equipment. Take precautions against build-up of electrostatic charges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Avoid contact with eyes, skin and clothing. Provide hand and eyes wash station near work area. Wash thoroughly after handling
Precautions	Use only under local exhaust or general ventilation.
Storage Conditions	Protect from direct sunlight Keep away from heat, flame, and all sources of ignition. Store in well-ventilated area. Keep container tightly closed. Store in a segregated and approved area

SECTION 8: EXPOSURE CONTROL / PERSONAL PROTECTION

Control Parameters TWA/ATEL/CEILING Biotic index:	
Engineering Controls	The use of closed system or local exhaust ventilation is recommended. Provide general ventilation Provide safety shower and eye wash station near work area.
Personal Protective equipment	Respiratory protection: Wear appropriate respirator when ventilation is inadequate. Hand Protection: Protective gloves. Eye protection: Safety glasses, goggles. Protective clothing: Safety helmet, protective clothing, safety boots, apron.

SAFETY DATA SHEET

Farbatone®

PRODUCT NAME: PEVA-S

PRINT DATE: 20-03-22

VERSION:1.0

SECTION 9: PHYSICAL & CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Thick liquid shape substance
Form/Color	Different colors
Odor	There is the mint smell
Boiling Point/Boiling Range	215.2°C
Flash Point	25.6°C
Spontaneous Temperature:	254°C
Exposure Limits	2.02%-7.9%
Vapor Pressure	10mmHg (20 °C)
Specific Gravity	3.38
Solubility in Water	0.870g
Decomposition Temperature	----
Volatilize rate(Butyl Acetate= 100)	----
Boiling Point/Boiling Range	215.2°C
Flash Point	25.6°C

SECTION 11: TOXICOLOGICAL INFORMATION

Inhalation	Vapor concentrations may be irritating to the eye and respiratory tract, and may cause headaches and dizziness
Skin Contact	Low order of toxicity, Frequent or prolonged contact may defat the dry skin leading to discomfort and dermatitis
Eye Contact	Will cause eye discomfort, may injure the eye tissue if do not remove immediately
Ingestion	Small amount of liquid aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary edema. Minimum toxicity.

SECTION 10: STABILITY AND REACTIVITY

Stability	Stable at normal temperatures and storage conditions.
Incompatible materials and conditions to avoid	Avoid contact with oxidizing materials such as peroxides, Chlorates, permanganates.
Hazardous Decomposition products	Thermal decomposition may produce various hydrocarbons and irritating, acid vapours.
Hazardous Polymerization	NOx, CO, Low molecular weight monomer etc.

SAFETY DATA SHEET



PRODUCT NAME: PEVA-S
PRINT DATE: 20-03-22
VERSION:1.0

SECTION 12: ECOLOGICAL INFORMATION

Environmental	This substance is highly volatile and will rapidly evaporate to the air mobility if released into the environment
Environmental Degradation	This substance does not biodegradable rapidly due to its low water solubility.
Precaution	When leaking and abandoning it, handling is noted because it might influence the environment. Deal so that neither the product nor the rinse water may flow to ground, the river and the drain ditch.

SECTION 13: DISPOSAL CONSIDERATION

Waste from Residues	This product is not suitable for disposal by either landfill or via municipal sewers, drains, natural streams or rivers. Whatever cannot be saved for recovery may be burned in an approved incinerator or disposed in approved waste facility. Ensure compliance with local, state, federal and national regulation.
Contaminated Packaging	Empty the container completely before disposal

SECTION 14: TRANSPORT INFORMATION

UN Number	1210: Printing ink
UN Classification	3: Flammable Liquid
Packing Group	III
ADR / RID Classification	3: Flammable Liquid
IMO / IMDG Classification	3: Flammable Liquid
ICAO / IATA Classification	3: Flammable Liquid

SECTION 15: REGULATORY INFORMATION

Apply Regulation Secure administration rules of perilous chemistry product » 2002.3.15

SECTION 16: OTHER INFORMATION

This information relater only to the material mentioned above. This information is believed to be accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made as to its accuracy, reliability, or completeness. It is the use's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.

SAFETY DATA SHEET

Farbatone[®]

PRODUCT NAME: PEVA-S

PRINT DATE: 20-03-22

VERSION:1.0